



**HoldZee**

Where Comfort meets Protection




# Where Comfort meets Protection

Holdwell Components, established on the pillar of protecting people by providing one stop solution for the entire railway track ecosystem from the past three decades is now inclined to contribute towards augmenting workforce safety as lifestyle in working environment.

Founded to foster the culture of safety, HoldZee caters to innovative offerings in head-to-toe Personal Protective Equipment designed to provide highest level of safety and consistently adhering to quality standards along with the dynamic requirements of the workplace.

Our Wide range of shoes covered under this catalog covers YOU from all sorts of accidents and prevents you from huge medical expenses. HoldZee's Bouncer's High Resilient Steel toes and Anti-Slip technology helps you and your team perform "on their toes".

**HOLDWELL COMPONENTS PVT.LTD**

 | 18, R.N. Mukherjee Road, 8th Floor, Kolkata-700001, West Bengal, India.

 | [info@holdzee.com](mailto:info@holdzee.com)

 | +91 33-40619006

 | [www.holdzee.com](http://www.holdzee.com)



## STYLE NAME: HZSS-01

1 YEAR WARRANTY

Standard Conform: IS: 15298:2016 Part-2  
& EN 20345:2011



|  |  |
|--|--|
| <b>TYPE</b>                                | Derby  |
| <b>SIZE</b>                                | 5-12   |
| <b>UPPER</b>                               | Grain/Split/CG/Alabama   |
| <b>UPPER THICKNESS</b>                     | 1.8mm – 2.2mm  |
| <b>SOLE</b>                                | Direct Moulded, PU Single/Double Density, heat resistance upto 120°C |
| <b>THICKNESS</b>                           | 8mm sole + 4mm   |
| <b>CLEATS (TOTAL 12MM) HEAL THICKNESS)</b> | 25mm-30mm + 4mm  |
| <b>INSOLE</b>                              | Soft EVA 4mm with Poly Drill Cloth/leather board                     |
| <b>CONSTRUCTION</b>                        | Direct PU Moulded & Toe Cap Lasted by Automatic machine              |
| <b>LAST</b>                                | 522 (Broad Shape)  |
| <b>LINING</b>                              | Cambrelle/Air Mesh (250 gsm)   |
| <b>LACES</b>                               | Nylon tubular/Round Flat, high tensile strength                      |
| <b>TOE CAP</b>                             | Steel/Fibre  |
| <b>ANTI-STATIC</b>                         | As per buyer requirement   |
| <b>ANTI-PENETRATION</b>                    | As per buyer requirement   |
| <b>PACKING</b>                             | 10/20 pairs a carton   |

|                         |   |
|-------------------------|---|
| <b>TYPE</b>             | Oxford-Regular  |
| <b>SIZE</b>             | 5-12  |
| <b>UPPER</b>            | Grain/Split/CG/Alabama  |
| <b>UPPER THICKNESS</b>  | 1.8mm - 2.2mm   |
| <b>SOLE</b>             | Direct Moulded, PU Single Density, Heat resistance upto 120°C |
| <b>THICKNESS</b>        | 8mm sole + 4mm Cleats (Total 12mm)                            |
| <b>INSOLE</b>           | Soft EVA 4mm with Poly Drill Cloth leather board              |
| <b>CONSTRUCTION</b>     | Direct PU Moulded & Toe Cap Lasted by Automatic machine       |
| <b>LAST</b>             | 522 (Broad Shape)   |
| <b>LINING</b>           | Cambrelle/Air Mesh (250 gsm)                                  |
| <b>LACES</b>            | Nylon tubular/Round Flat, high tensile strength               |
| <b>ANTI-STATIC</b>      | As per buyer requirement                                      |
| <b>ANTI-PENETRATION</b> | As per buyer requirement                                      |
| <b>PACKING</b>          | 10/20 pairs a carton  |

## STYLE NAME: HZSS-02

1 YEAR WARRANTY

Standard Conform: IS: 15298:2016 Part-2  
& EN 20345:2011



## STYLE NAME: HZSS-02H

1 YEAR WARRANTY

Standard Conform: IS: 15298:2016 Part-2  
& EN 20345:2011



|  |  |
|--|--|
| <b>TYPE</b>                                | Oxford-High Ankle  |
| <b>SIZE</b>                                | 5-12   |
| <b>UPPER</b>                               | Grain/Split/CG/Alabama   |
| <b>UPPER THICKNESS</b>                     | 1.8mm – 2.2mm  |
| <b>SOLE</b>                                | Direct Moulded, PU Single/Double Density, Heat resistance upto 120°C |
| <b>THICKNESS</b>                           | 8mm sole + 4mm   |
| <b>CLEATS (TOTAL 12MM) HEAL THICKNESS)</b> | 25mm-30mm + 4mm, Cleats (Total 34mm)                                 |
| <b>INSOLE</b>                              | Soft EVA 4mm with Poly Drill Cloth/leather board                     |
| <b>CONSTRUCTION</b>                        | Direct PU Moulded & Toe Cap Lasted by Automatic machine              |
| <b>LAST</b>                                | 522 (Broad Shape)  |
| <b>LINING</b>                              | Cambrelle/Air Mesh (250 gsm)   |
| <b>LACES</b>                               | Nylon tubular/Round Flat, high tensile strength                      |
| <b>TOE CAP</b>                             | Steel/Fibre (EN 12368 Marked Imported Impact Resistance 100/200J)    |
| <b>ANTI-STATIC</b>                         | As per buyer requirement   |
| <b>ANTI-PENETRATION</b>                    | As per buyer requirement   |
| <b>PACKING</b>                             | 10/20 pairs a carton   |

|                         |  |
|-------------------------|--|
| <b>TYPE</b>             | Derby  |
| <b>SIZE</b>             | 5-12 (39-46)   |
| <b>UPPER</b>            | Grain/Split Leather  |
| <b>UPPER THICKNESS</b>  | 1.8mm – 2.2mm  |
| <b>OUTSOLE</b>          | Nitrile Rubber Sole (Heat Resistance upto 300°C)                               |
| <b>INSOLE</b>           | Soft EVA 4mm with cloth pasting  |
| <b>CONSTRUCTION</b>     | Direct Vulcanizing Process & Toe Cap Lasted by Automatic Machine               |
| <b>LAST</b>             | 522 (Broad Shape)  |
| <b>LINING</b>           | Skin Fit (250 gsm)   |
| <b>LACES</b>            | 90cm Round/Flat  |
| <b>LACES</b>            | Steel/Fibre – 200 Joule, (EN 12368 Marked Imported Impact Resistance 100/200J) |
| <b>ANTI-PENETRATION</b> | As per buyer requirement   |
| <b>PACKING</b>          | 10/20 pairs a carton   |

## STYLE NAME: HZS-N Series

1 YEAR WARRANTY

Standard Conform: IS: 15298:2016 Part-2  
& EN 20345:2011



## STYLE NAME: HZSS-02DD







































1 YEAR WARRANTY

Standard Conform: IS: 15298:2016 Part-2  
& EN 20345:2011



|                         |  |
|-------------------------|--|
| <b>TYPE</b>             | Oxford-Double Density                                      |
| <b>SIZE</b>             | 5-12   |
| <b>UPPER</b>            | Grain/Split/CG/Alabama                                     |
| <b>UPPER THICKNESS</b>  | 1.8mm – 2.2mm  |
| <b>SOLE</b>             | Direct Moulded, Double Density, Heat resistance upto 120°C |
| <b>THICKNESS</b>        | 8mm sole + 4mm cleats (Total 12mm)                         |
| <b>INSOLE</b>           | Soft EVA 4mm with Poly Drill Cloth/leather board           |
| <b>CONSTRUCTION</b>     | Direct PU Moulded & Toe Cap Lasted by Automatic machine    |
| <b>LAST</b>             | 522 (Broad Shape)  |
| <b>LINING</b>           | Cambrelle/Air Mesh (250 gsm)                               |
| <b>LACES</b>            | Nylon tubular/Round Flat, high tensile strength            |
| <b>ANTI - STATIC</b>    | As per buyer requirement                                   |
| <b>ANTI-PENETRATION</b> | As per buyer requirement                                   |
| <b>PACKING</b>          | 10/20 pairs a carton                                       |

## SPECIFICATION CATEGORIES OF SAFETY FOOTWEAR

| STANDARD | FEATURES  |
|----------|---|
| NS       | Non-safety, does not comply with EN ISO20345  |
| SB       | Safety toe cap protecting against 200J impact     |
| SBP      | As per SB, with penetration resistant midsole      |
| S1       | As per SB, with anti-static properties fuel oil resistant, energy absorbing heel      |
| S1P      | As per S1, with penetration resistant midsole        |
| S2       | As per S2, with water resistant upper         |
| S3       | As per S2, with penetration resistant midsole        |
| S4       | As per S1, with waterproof seal        |
| S5       | As per S4, with penetration resistant midsole         |

### FEATURES



Breathable leather



Steel Midsole



Anti Slip



Shock Absorption



200 Jules Toe Cap



Water Repellent



Anti Static



Oil Resistant